



US005954839A

**United States Patent** [19]  
**Park et al.**

[11] **Patent Number:** 5,954,839  
 [45] **Date of Patent:** Sep. 21, 1999

[54] **ERROR PROTECTION METHOD FOR MULTIMEDIA DATA**

[75] **Inventors:** Dong-seek Park, Daegu, Rep. of Korea; John Villasenor, Santa Monica, Calif.; Feng Chen, Irvine, Calif.; Max Luttrell, Santa Monica, Calif.; Brendan Dowling, Malibu, Calif.

[73] **Assignees:** Samsung Electronics Co., Ltd., Kyungki-do, Rep. of Korea; The Regents of the University of California, Oakland, Calif.

[21] **Appl. No.:** 08/782,174

[22] **Filed:** Jan. 14, 1997

[51] **Int. Cl.<sup>6</sup>** ..... G06F 11/00

[52] **U.S. Cl.** ..... 714/825; 714/775; 714/746; 714/748; 714/751; 375/364; 375/368

[58] **Field of Search** ..... 371/72, 30, 32, 371/35, 42, 37.02, 37.05; 357/206; 65/32.5; 364/514; 375/364, 368; 369/59

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

4,914,699	4/1990	Dunn et al.	65/32.5
5,157,687	10/1992	Tymes	357/206
5,671,156	9/1997	Weerackody et al.	364/514
5,689,439	11/1997	Weerackody et al.	364/514

**FOREIGN PATENT DOCUMENTS**

0 479 296 A1 4/1992 European Pat. Off. .... H03M 9/00

**OTHER PUBLICATIONS**

Gold et al., "Error Correction strategies for data Broadcasting", IEEE, pp. 323-327, 1988.

Pingzhi et al., "Linear Unequal Error-Protection Array Codes", IEEE, pp. 333-334, Jan. 1988.

Shiozaki, "Unequal Error Protection of PCM Signals by Self-Orthogonal Convolutional Codes", IEEE, pp. 289-290, 1989.

Baker et al., "Mode S System Design and Architecture", IEEE, pp. 1689-1694, 1989.

Stephen B. Wicker, "Adaptive Rate Error Control Through the Use of Diversity Combining and Majority Logic Decoding in a Hybrid-ARQ Protocol", IEEE, pp. 29.6.1.-29.6.6., 1989.

*Primary Examiner*—Reba I. Elmore

*Assistant Examiner*—McDieunel Marc

*Attorney, Agent, or Firm*—Sughrue, Mion, Zinn, Macpeak & Seas, PLLC

[57] **ABSTRACT**

An error protection method for multimedia improves data recovery and channel throughput in channels which cause a random error and a burst error by using a rate compatible punctured convolutional code (RCPC) and an automatic retransmission on request (ARQ). In a process of decoding a plurality of packets of given information, the error protection method includes the steps of a) decoding one of the plurality of packets, b) decoding another packet when an error occurs during the decoding in step a), c) decoding a combination of the packets from steps a) and b) or a third packet when an error occurs in step b), and d) repeating step c) until the decoding error no longer occurs. The error protection method has the characteristics of both Type-1 and Type-2 ARQ methods. Therefore, one can obtain constant channel throughput in a channel containing burst errors, a channel containing random errors, and a channel in which the two types of error patterns coexist simultaneously.

14 Claims, 3 Drawing Sheets

